

**Global Parts Order Processing  
Material Safety Data Sheet  
MORAN ST. CLAIR CHRYSLER JEEP**

C H R Y S L E R

HAZARD COMMUNICATION SHEET

199835 DRAFT PART/COMMTY CD: 05127382AA  
PREPARATION DATE: 02-25-04 STNDRD: N/AV SUPPLIER: 37637 MFGR: 03500  
OSHA HAZ: YES HAZWOPER HAZ: YES CONS PROD/HAZ SUB: YES

\*\*\* SECTION 01 - PRODUCT INFORMATION \*\*\*

MFG BY: PART SALES & SERVICE CHRYSLER  
26311 LAWRENCE AVE CENTERLINE MI 48015  
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888  
DIST BY: PART SALES & SERVICE CHRYSLER  
26311 LAWRENCE AVE CENTERLINE MI 48015  
EMERGENCY PHONE: 248-512-8002 AFTER HOURS: 248-576-8888  
CHRYSLER INDUSTRIAL HYGIENE: 248-512-8260 AFTER HOURS: 248-576-8888  
BRAND NAME: SHELL ATF 3403-M115  
MFG ID : N/AV  
DESCRIPTION: FLUID-AUTOMATIC TRANSMISSION

\*\*\* SECTION 02 - INGREDIENTS \*\*\*

HAZARDOUS INGREDIENTS: PERCENT  
COMM NAME / CAS NO & CHEM NAME: BY WGT OSHA ACGIH CHRYS UNITS NOTATIONS  
\*\*\*EXISTING INGREDIENTS\*\*\*  
DISTILLATES (PETROLEUM), SOLVENT- 60-100 W 5 5 5 MG/M3 I1 N1  
064741-89-5 DISTILLATES, PETROLE L N/AP 10 10 A2  
HYDROTREATED LIGHT NAPHTHENIC DIS 60-100 W 5 5 5 MG/M3 I1 N1  
064742-53-6 DISTILLATES, PETROLE L N/AP 10 10 A2  
DISPERSANT 10-30 W N/AV N/AV N/AV N/AV  
000756-00-2C DISPERSANT  
INHIBITORS, ORGANIC 10-30 W N/AV N/AV N/AV N/AV  
000950-00-2C INHIBITORS, ORGANIC  
GENERIC DESC: MIXTURE(S) OF THE FOLLOWING: PETROLEUM DISTILLATE(S), WAX,  
ADDITIVES AND XYLENE.

\*\*\* SECTION 03 - PHYSICAL DATA \*\*\*

BOILING POINT : N/AV SOLUB IN WATER: N/AV  
VAPOR PRESSURE: < 0 MM HG ATN/AV EVAP. RATE: N/AV REF: N/AV  
VAPOR DENSITY : N/AV SPECIFIC GRAVITY: 0.890 AT 60 F  
PH AT FULL STRENGTH: N/AV PH AT REC. DILUT: N/AV  
%VOLATILE BY VOL : N/AV VOLATILE ORGANIC COMP: N/AV N/AV  
ODOR THRESHOLD: N/AV PPM FOR % POPULATION  
FREEZING POINT: N/AV COEFF. OF WATER/OIL DIST: N/AV  
APPEARANCE & ODOR: STATE: LIQUID..... COLOR: RED..... ODOR: HYDROCARBON.....  
ODOR: PETROLEUM.....

**Global Parts Order Processing**  
**Material Safety Data Sheet**  
**MORAN ST. CLAIR CHRYSLER JEEP**

\*\*\* SECTION 04 - FIRE AND EXPLOSION DATA \*\*\*

FLASH POINT: 374 F COC IGN TEMP: N/AV LEL: N/AV UEL: N/AV

SPECIAL FIRE & EXPLOSION HAZARDS:

PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER. DO NOT USE WATER IN STRAIGHT STREAMS.

EXTINGUISHING MEDIA:

WATER FOG, FOAM, DRY CHEMICAL OR CARBON DIOXIDE.

SPECIAL FIREFIGHTING PROCEDURES:

USE PROTECTIVE CLOTHING. USE SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SENSITIVE TO MECHANICAL IMPACT?: N/AV SENSITIVE TO STATIC DISCHARGE?: N/AV

HAZARDOUS COMBUSTION PRODUCTS:

OXIDES OF NITROGEN, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS, ORGANIC COMPOUNDS, CARBON MONOXIDE AND CARBON DIOXIDE.

FLAME PROJECTION: N/AP

\*\*\* SECTION 05 - HEALTH HAZARD DATA \*\*\*

EFFECTS OF OVEREXPOSURE - ACUTE & CHRONIC:

<<---EYE CONTACT--->> MINOR IRRITATION. <<---SKIN CONTACT--->> DIRECT CONTACT MAY PRODUCE THE FOLLOWING: MINOR IRRITATION.. PROLONGED CONTACT MAY PRODUCE THE FOLLOWING: OIL ACNE, FOLLICULITIS OR DERMATITIS.

<<---INHALATION--->> IF HEATED TO HIGH TEMPERATURE VAPOR MAY PRODUCE THE FOLLOWING: IRRITATION OF UPPER RESPIRATORY TRACT. <<---INGESTION--->> NO KNOWN EFFECTS. HOWEVER, INGESTION IS NOT RECOMMENDED. <<---MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY THIS PRODUCT--->> SKIN DISORDERS AND LUNG OR RESPIRATORY TRACT DISORDERS.

EMERGENCY FIRST AID PROCEDURES:

<<---EYE CONTACT--->> RINSE EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER, OCCASIONALLY LIFTING BOTH UPPER AND LOWER LIDS. CONTINUE FOR 15 MINUTES. CONTACT A PHYSICIAN. <<---SKIN CONTACT--->> REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF CONDITION PERSISTS, CONSULT A PHYSICIAN. <<---INHALATION--->> REMOVE TO FRESH AIR AT ONCE. ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. CARDIAC RESUSCITATION IF INDICATED. CONTACT A PHYSICIAN. <<---INGESTION--->> LARGE QUANTITIES-DO NOT INDUCE VOMITING-CALL PHYSICIAN IMMEDIATELY.

\*\*\* SECTION 06 - REACTIVITY DATA \*\*\*

STABILITY: STABLE

CONDITIONS TO AVOID:

HIGH TEMPERATURE AND SPARKS OR OPEN FLAME.

MATERIALS TO AVOID:

OXIDIZABLE MATERIALS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

**Global Parts Order Processing  
Material Safety Data Sheet  
MORAN ST. CLAIR CHRYSLER JEEP**

POLYMERIZATION CONDITIONS TO AVOID:

POLYMERIZATION WILL NOT OCCUR.

HAZARDOUS DECOMPOSITION PRODUCTS:

OXIDES OF NITROGEN, OXIDES OF SULFUR, OXIDES OF PHOSPHORUS, ORGANIC  
COMPOUNDS, CARBON MONOXIDE AND CARBON DIOXIDE.

-----  
\*\*\* SECTION 07 - SPILL OR LEAK PROCEDURES \*\*\*  
-----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

LARGE SPILL-DO NOT FLUSH INTO SEWER SYSTEM. WEAR PROTECTIVE CLOTHING. WEAR  
RESPIRATORY PROTECTION. STOP SPILL AT SOURCE. CONTAIN WITH DIKE. REMOVE  
SPILL BY USING A VACUUM TRUCK. PUMP INTO SALVAGE TANK. PREVENT GROUNDWATER  
CONTAMINATION. RESIDUE-ABSORB ON SAND OR VERMICULITE FLUSH AREA WITH WATER.

WASTE DISPOSAL METHODS:

DISPOSE OF IN A MANNER CONSISTENT WITH STATE, PROVINCIAL, LOCAL, AND  
FEDERAL DISPOSAL REGULATIONS. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR  
MAY ENTER SEWERS, WATERCOURSES OR EXTENSIVE LAND AREAS.

-----  
\*\*\* SECTION 08 - SPECIAL PROTECTION \*\*\*  
-----

RESPIRATORY PROTECTION:

ORGANIC VAPOR RESPIRATOR OR AIR-SUPPLIED RESPIRATOR. THIS EQUIPMENT MAY BE  
NEEDED IF SIGNIFICANT VAPORS OR MIST ARE GENERATED.

VENTILATION TYPE:

GOOD GENERAL VENTILATION.

PROTECTIVE GLOVES:

RECOMMENDED. NITRILE RUBBER GLOVES.

EYE PROTECTION:

RECOMMENDED. CHEMICAL GOGGLES.

OTHER PROTECTIVE EQUIPMENT:

CLOTHING (SAME MATERIAL AS GLOVES). ALL SKIN CONTACT MUST BE AVOIDED.  
PROTECTIVE EQUIPMENT MUST BE WORN AT ALL TIMES DURING PRODUCT USE IF SKIN  
CONTACT IS POSSIBLE.

-----  
\*\*\* SECTION 09 - SPECIAL PRECAUTIONS \*\*\*  
-----

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE:

AVOID SKIN CONTACT. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.  
WASH THOROUGHLY AFTER HANDLING. LEATHER CLOTHING AND SHOES WILL BE DAMAGED  
BY THIS PRODUCT. STORE IN A COOL, DRY PLACE. STORE IN A WELL VENTILATED  
AREA. KEEP AWAY FROM OPEN FLAME. AVOID USING OR STORING AT HIGH  
TEMPERATURES.

OTHER PRECAUTIONARY MEASURES:

MAINTAIN GOOD HOUSEKEEPING AND HYGIENIC PRACTICES.

-----  
\*\*\* SECTION 10 - WASTE LABELING INFORMATION \*\*\*  
-----

60175000  
s81433c

**Global Parts Order Processing**  
**Material Safety Data Sheet**  
**MORAN ST. CLAIR CHRYSLER JEEP**

May 30, 2012  
15:27

DOT LABELING INFORMATION (49 CFR 100-199)

ID#: N/AP    ERG#:            HAZARD CLASS - PRMY: N/AP    PACKING GROUP: N/AP  
NOT HAZARDOUS PER DOT REGULATIONS

RCRA INFORMATION (40 CFR 122-124, 260-265)

INFORMATION UNAVAILABLE AT THIS TIME